CLAIMS

What is claimed is:

1.   1.   An echo/near-end-crosstalk cancellation system for a
2.   bi-directional data communications system comprising:

3.   a first finite impulse response (FIR) filter;

4.   a second FIR filter coupled to the first FIR filter;

5.   a data partitioning means for partitioning a data
6.   signal, wherein a first portion of the partitioned data
7.   signal is processed by the first FIR filter, and a second
8.   portion of the partitioned data signal is processed by the
9.   second FIR filter; and

10.   a combination means for subtracting the outputs of the
11.   first and second FIR filters from the data signal to provide
12.   echo/near-end-crosstalk (E/N) cancellation.

13.

1.   2.   The system according to Claim 1, further
2.   comprising a control means for adjusting the plurality of
3.   filter output values.

4.

1.   3.   The system according to claim 1, wherein the first
2.   FIR filter and the second FIR filter are each implemented as
3.   a separate integrated circuit.

4.

14

1   4.   The system according to claim 1, wherein the first

2   FIR filter is comprised of a plurality of filter elements.

3

1   5.   The system according to claim 1, wherein the

2   second FIR filter is comprised of a plurality of filter

3   elements.

4

1   6.   The system according to claim 1, wherein the data

2   partitioning means comprises a plurality of conductors for

3   conducting the first portion of the data signal to the first

4   FIR filter and the second portion of the data signal to the

5   second FIR filter.

6

1   7.   The system according to claim 6, wherein the first

2   portion of the partitioned data signal is comprised of the

3   least significant bits (LSBs) of the data signal and the

4   second portion is comprised of the most significant bits

5   (MSBs) of the data signal.

6

1   8.   The system according to claim 6, wherein the first

2   portion of the partitioned data signal negates a first

3   portion of an E/N signal generated as a result of the

4   transmission of the data signal.

1   9.   The system according to claim 8, wherein the

2 second portion of the partitioned data signal negates a

3 second portion of an E/N signal generated as a result of the

4 transmission of the data signal, wherein the second portion

5 of the E/N signal is not included in the first portion.

6

1   10.   The system according to claim 1, wherein the first

2 and second FIR filters are adaptive type filters.

3

1   11.   The system according to claim 1, wherein the first

2 and second FIR filters are non-adaptive type filters.

3

1   12.   The system according to claim 1, wherein the first

2 and second FIR filters are digital filters.

3

1   13.   The system according to claim 1, wherein both the

2 first and second FIR filters are configured identically in

3 direct form.

4

1   14.   The system according to claim 1, wherein both the

2 first and second FIR filters are configured identically in

3 transpose form.

15. The system according to claim 1, wherein the first
and second FIR filters are configured differently, with one
being in direct form and the other being in transpose form.

16. The system according to claim 1, wherein the
control means for adjusting the plurality of filter output
values comprises a multi-tap delay line including a
plurality of taps, wherein at least one programmable delay
line is interposed between two of the plurality of taps.

17. The system according to claim 1, wherein the
control means for adjusting each of the plurality of filter
output values comprises at least one holding register in
each FIR filter for implementing a unique one of a plurality
of adaptive delays.

18. The system according to claim 1, wherein the first
and second FIR filters filter the data signal using either
fixed or floating point numbers.

19. A method for partitioning data words in an
echo/near-end-crosstalk cancellation circuit for a
communications system, comprising the steps of:

4   determining a first bit resolution from a predetermined

5   number of a plurality of echo/near-end-crosstalk (E/N)

6   signals having a lowest amplitude;

7   determining a second bit resolution by subtracting the

8   first bit resolution from a bit resolution of a single

9   signal from a plurality of E/N signals having a highest

10   amplitude; and

11   partitioning the plurality of E/N signals such that a

12   first portion is processed by a first FIR filter having a

13   data path identical to the first bit resolution, and a

14   second portion comprised of bits having a data size

15   exceeding the bit width of the first FIR filter is processed

16   by a second FIR filter having a data path identical to the

17   second bit resolution.

18

1   20. The method according to claim 19, wherein the

2   predetermined number of signals comprises a majority of the

3   plurality of E/N signals.

4

1   21. The method according to claim 20, wherein the

2   predetermined number of signals comprises three quarters of

3   the plurality of E/N signals.

4

1   22. A method for partitioning a data signal,

2   comprising the steps of:

3   determining from a plurality of echo/near-end-crosstalk

4   (E/N) signals a maximum bit resolution associated with a

5   single signal having a highest amplitude;

6   selecting a first FIR filter and a second FIR filter

7   each having a bit resolution equal to at least half of the

8   maximum bit resolution; and

9   partitioning the plurality of E/N signals such that a

10   first portion is processed by the first FIR filter, and a

11   second portion comprised of bits having a data size greater

12   than the bit width of the first FIR filter are processed by

13   the second FIR filter.